

Be Original.

## PN-LC862 / PN-LC752 / PN-LC652













To card the card throat the card throat thro









# **OUTSTANDING FEATURES:**



#### Multi-touch Screen

Write directly on the interactive screen with multi-touch technology, allow contact up to 20 simultaneous touch points at the same time without any gap, Zero Bonding.



#### **Smart Interactive Software (Touch Viewing)**

Leverage the power of Touchview software to collect, manipulate, and organize files directly on the screen without the need to open separate applications, saving time and enhancing productivity.



#### **Dual Tip Passive Pen x 2**

The special pen features two tips (8mm and 3mm), allowing you to use it as two different writing tools without needing to switch or interrupt your workflow. Easily switch between two colors without changing settings.

### **SPECIFICATIONS - IWB**

MODEL			PN-LC652/LC752/LC862
Size			65"/75"/86"
Installation			Landscape
Brightness (cd/m)			450
View Angle			178°
Touchscreen	Touch Technology		IR
	GAP		Zero bonding
	Multi Touch		20 points
	Pen tip size (tip / back)		3mm/8mm
	Touch Pen		Dual-tip Passive pen x2
	Response time		8ms
Terminals	Input Terminals	HDMI	X3 (Front:1,Rear:2)
		USB type-C	x1 (DP1.2 Alt, PD 65W)
		DisplayPort	x1
		VGA	x1
		Component	No
		AV	x1
		Audio	x1
	Output Terminals	Video	HDMI x1
		Audio	mini jack x1, S/PDIF x1
	System	LAN	x1
		USB	Front x2 (USB 3.0) Rear x2 (USB 3.0)
		RS-232C	x1
		SD Card Slot	No
System	CPU		Arm Cortex quad A55
	Memory / Internal Storage		4GB /16GB
	os		Android Ver 11 (Not representable)
	Wireless LAN		IEEE 802.11 ac/n/g/a/b
	Bluetooth		4.2
	Expansion Slot		OPS
Speaker Output			15W+15W (Front)
Continuous operation time			16H
Application	Whiteboard		Multifunctional whiteboard
	Web Browser		✓
	Wireless Cast (EShare)		√ max 9
	PDF Viewer		✓
	Screen Capture		✓
Application	Screen Recorder		✓
	Timer		✓
	Calculator		✓
	Vote		✓
	Media Player		✓
Othors	ЕМІ		Class B
Others	Pen tray		√

<sup>\*1</sup> Without glasses. Brightness depends on the input mode and other picture settings. Brightness level will decrease slightly during product use. Due to physical limitations of the device, it is not possible to maintain a constant exact brightness level.

- \*3 Approximate distance at which the glass panel can withstand the impact of a 500 gram iron ball dropped on its center.
- \*4 Use a commercially available connection cable for PC and other video connections.
- \*5 The AC power cord is an input type. The cable is bundled (3 pins).
- \*6 Temperature conditions may change when the monitor is used with an optional device. In such cases, check the temperature conditions specified by the optional device.
- \*7 Check the requirements of the computer and other connected devices and make sure that all requirements are met.
  - \* The design and specifications are subject to change without notice. For further information, please contact our sales representatives.





No. 159, Vo Nguyen Giap Street, Thao Dien Ward, Thu Duc city, Ho Chi Minh city Hotline: 1-800-1594 Website: vn.sharp

Service email: sbs-service@svn.sharp-world.com





<sup>\*2</sup> The touch sensor around the LCD panel is not included.